

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application, and entry of this listing of claims is respectfully requested:

**Listing of Claims**

1. (Currently Amended): A method for testing the crimped state of a test terminal on the basis of a waveform of ~~[[the]]~~ characteristic values obtained in the process of crimping the test terminal on a core of an electric wire, comprising the steps of:

acquiring a reference waveform from ~~[[the]]~~ a characteristic waveform when ~~[[the]]~~ a first terminal has been crimped normally, and dividing the reference waveform into first plural reference waveform segments, the reference waveform showing changes in load corresponding to time elapsed when the first terminal is crimped normally, each of the first plural reference waveform segments corresponding to a segment of time elapsed when the first terminal is crimped normally;

dividing ~~the a~~ characteristic waveform obtained when ~~[[a]]~~ the test terminal ~~to be tested~~ is crimped on the electric wire into ~~[[a]]~~ second plural waveform segments corresponding to those of the reference waveform; and

deciding whether or not the crimped state of the test terminal is good on the basis of the first reference waveform segments of the reference waveform and the second waveform segments of the characteristic waveform obtained when the test terminal is crimped.

1           2. (Currently Amended): The [[A]] method of testing the crimped state of a test terminal  
2 according to claim 1, wherein singular points of the reference waveform are previously acquired on  
3 the basis of increments of the reference waveform; and said first reference waveform segments  
4 contain said singular points.

1           3. (Currently Amended): The [[A]] method of testing the crimped state of a test terminal  
2 according to claim 1, wherein singular points of the reference waveform are previously acquired on  
3 the basis of increments of the reference waveform; and said first reference waveform segments are  
4 located between the singular points.

1           4. (Currently Amended): A method for testing the crimped state of a test terminal on the  
2 basis of a waveform of [[the]] characteristic values obtained in the process of crimping the test  
3 terminal on a core of an electric wire, comprising the steps of:

4           acquiring a reference waveform from [[the]] a characteristic waveform when [[the]] a first  
5 terminal has been crimped normally, the reference waveform showing changes in load corresponding  
6 to time elapsed when the first terminal is crimped normally;

7           acquiring singular points of the reference waveform on the basis of [[the]] increments  
8 thereof, the increments corresponding at least to a maximum change in load per unit time and a zero  
9 change in load per unit time;

10          acquiring ~~second~~ first reference waveform segments which are segments containing the

11 singular points;

12 acquiring second waveform segments containing ~~[[the]]~~ points corresponding to said singular  
13 points in the ~~characteristic~~ waveform obtained when the test terminal ~~to be tested~~ has been crimped  
14 on the electric wire; and

15 deciding whether or not the crimped state of the test terminal is good on the basis of said  
16 ~~second~~ first reference waveform segments and said second waveform segments.

PS  
K  
Con  
1 5. (Currently Amended): The ~~[[A]]~~ method of testing the crimped state of a test terminal  
2 according to claim 2, wherein said singular points are points where the ~~increment~~ increments of said  
3 reference waveform ~~[[is]]~~ correspond to at least one selected from among a maximum change in load  
4 per unit time ~~[[or]]~~ and a zero change in load per unit time.

1 6. (Currently Amended): A method for testing the crimped state of a test terminal on the  
2 basis of a waveform of ~~[[the]]~~ characteristic values obtained in the process of crimping the test  
3 terminal on a core of an electric wire, comprising the steps of:

4 acquiring a reference waveform from ~~[[the]]~~ a characteristic waveform when ~~[[the]]~~ a first  
5 terminal has been crimped normally, and acquiring reference characteristic values at regular intervals  
6 of the reference waveform, the reference waveform showing changes in load corresponding to time  
7 elapsed when the first terminal is crimped normally;

8 acquiring ~~[[the]]~~ characteristic values of the ~~characteristic~~ waveform obtained when the test

terminal ~~to be tested~~ has been crimped on the electric wire, at said regular intervals; and  
deciding whether or not the crimped state of the test terminal is good on the basis of said  
reference characteristic values and the characteristic values of the waveform obtained when the test  
terminal has been crimped.

7. (Currently Amended): The [[A]] method of testing the crimped state of a test terminal  
according to claim 2, wherein said electric wire has a coating for coating said core,  
said test terminal has caulking legs for caulking said core,  
a first poorness waveform is acquired from the waveform obtained when the test terminal is  
crimped when said ~~caulking~~ caulking legs caulk said coating as well as said core, and  
a first singular point of said singular points is acquired from said reference waveform and  
said first poorness waveform.

8. (Currently Amended): The [[A]] method of testing the crimped state of a test terminal  
according to claim 7, wherein said first singular point is defined by a point where [[the]] a  
characteristic value of said first poorness waveform exceeds that of said reference waveform as the  
time of the crimping of the test terminal ~~a crimping operation~~ elapses.

9. (Currently Amended): The [[A]] method of testing the crimped state of a test terminal  
according to claim 2, wherein

3 said core is composed of a plurality of conductors tied up in a bundle;

4 said test terminal has caulking legs for caulking said core;

5 a second poorness waveform is acquired from the ~~characteristic~~ waveform obtained when  
6 the test terminal is crimped when said caulking legs caulk conductors whose number is smaller than  
7 that when the first terminal has been normally crimped; and

8 a second singular point is acquired from said reference waveform and said second poorness  
9 waveform.

1 10. (Currently Amended): The ~~[[A]]~~ method of testing the crimped state of a test terminal  
2 according to claim 9, wherein said second singular point is defined by a point where ~~[[the]]~~ a  
3 characteristic value of said ~~first~~ second poorness waveform falls below that of said reference  
4 waveform as the time of the crimping of the test terminal ~~a crimping operation~~ elapses.

---